


Specifications



MODELS	GL™-4		GL™-8		GL™-10		GL™-12	
MEASUREMENTS	Metric	US	Metric	US	Metric	US	Metric	US
⚠ Height - stowed ^{1, 2, 3}	1.72 m	5 ft 7.5 in	1.72 m	5 ft 7.5 in	2.00 m	6 ft 6.5 in	2.31 m	7 ft 7 in
maximum forks down	1.26 m	4 ft 1.5 in	2.51 m	8 ft 3 in	3.01 m	9 ft 10.5 in	3.66 m	12 ft
maximum forks up	1.80 m	5 ft 11 in	3.06 m	10 ft 0.5 in	3.56 m	11 ft 8 in	4.20 m	13 ft 9.5 in
minimum forks down	0.09 m	3.5 in	0.09 m	3.5 in	0.05 m	2 in	0.05 m	2 in
STANDARD BASE								
B Length - stowed	0.30 m	1 ft	0.30 m	1 ft				
operating	0.88 m	2 ft 10.75 in	0.88 m	2 ft 10.75 in				
(F) Width: outside	0.63 m	2 ft 0.75 in	0.63 m	2 ft 0.75 in				
Weight - standard caster options	51 kg	113 lbs	60 kg	132 lbs				
pneumatic caster options	53 kg	117 lbs	62 kg	136 lbs				
STRADDLE BASE								
Length - stowed	0.49 m	1 ft 7.25 in						
operating	1.09 m	3 ft 7 in						
Width - stowed4	0.73 m	2 ft 4.75 in						
maximum ⁴	1.10 m	3 ft 7.5 in						
maximum inside	0.91 m	3 ft						
Weight - standard caster options	57 kg	126 lbs	66 kg	145 lbs	68 kg	149 lbs	70 kg	154 lbs
pneumatic caster options	59 kg	130 lbs	68 kg	149 lbs	69 kg	153 lbs	72 kg	158 lbs
4-point caster option	63 kg	139 lbs	72 kg	158 lbs	73 kg	162 lbs	76 kg	167 lbs
COUNTERWEIGHT BASE								
Length - operating	0.72 m	2 ft 4.5 in	0.72 m	2 ft 4.5 in	0.72 m	2 ft 4.5 in		
Width - stowed4	0.73 m	2 ft 4.75 in	0.73 m	2 ft 4.75 in	0.73 m	2 ft 4.75 in		
maximum ⁴	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in		
maximum inside	0.91 m	3 ft	0.91 m	3 ft	0.91 m	3 ft		
Weight - standard caster options	178 kg	392 lbs	186 kg	411 lbs	196 kg	433 lbs		
PRODUCTIVITY								
Load height minimum	0.09 m	3.5 in						
Ground clearance - centre ^{1, 2, 3}	0.02 m	0.75 in						
Average cranks - standard winch	38/m	11.5/ft	38/m	11.5/ft	38/m	11.5/ft	38/m	11.5/ft
electric winch	0.05 m/sec	2 in/sec						
Fork length	0.57 m	1 ft 10.5 in						
Fork width	0.52 m	1 ft 8.5 in						
Load platform length	0.58 m	1 ft 11 in						
Load platform width	0.56 m	1 ft 10 in						
Load capacity at						<u> </u>		
12 in (30 cm) load centre	227 kg	500 lbs	181 kg	400 lbs	159 kg	350 lbs	159 kg	350 lbs
Boom length	0.51 m	20.19 in						
Boom attachment points	34 / 48 cm	13.25 / 19 in	34 / 48 cm	13.25 / 19 in	34 / 48 cm	13.25 / 19 in	34 / 48 cm	13.25 / 19 in

POWER

Power source reversible standard winch or electric winch

¹ The 10 in pneumatic rear wheel option will add 2.5 cm (1 in) to these specifications.

² The counterweight base will add 2.5 cm (1 in) to these specifications.

³ The 4-point caster option B will add 2.5 cm (1 in) to these specifications.

⁴ Outside dimensions.

MATERIAL LIFTS

Genie® Lift™



Features

STANDARD FEATURES

MEASUREMENTS

GL™-4

- 1.80 m (5 ft 11 in) maximum lift height
- Up to 227 kg (500 lbs) load capacity

GL™-8

- 3.06 m (10 ft 0.5 in) maximum lift height
- Up to 181 kg (400 lbs) load capacity

GL™-10

- 3.56 m (11 ft 8 in) maximum lift height
- Up to 159 kg (350 lbs) load capacity

GL™-12

- 4.20 m (13 ft 9.5 in) maximum lift height
- Up to 159 kg (350 lbs) load capacity

PRODUCTIVITY

- Standard forks
- Portable and compact design
- Lightweight durable aluminium construction
- Single door access
- Durable standard steel forks
- 20 cm (8 in) non-marking rear wheels and 5 cm (2 in) dual wheel front swivel casters (standard and straddle base only)
- 12 cm (5 in) rear swivel casters with side brakes and 10 cm (4 in) fixed front wheels (counterweight base only)
- · Loads easily into a ute for transporting
- Hold-down mechanism secures carriage during transport

POWER

- Standard winch
- Reversible winch handle for easy storage

OPTIONS & ACCESSORIES

PRODUCTIVITY

- Counterweight base (GL[™]-4, -8, -10)
- Load platform
- Boom
- Aluminum ladder (standard and straddle base only)
- Pneumatic rear tyres (standard and straddle base only)
- Foot-release brake (standard and straddle base only)
- Caster options
- Straddle base

POWER OPTIONS

- Electric winch (straddle and counterweight base only)
- Winch operates while ladder is in use or stowed
- Caster option kit required for use with Straddle bases
- Electric winch option comes standard with battery and automatic charger that shuts off when fully charged



Genie Australia – Toll free number 1800 788 633

Brisbane (Head Office) 33 Kimberley Street Darra QLD 4076 **Sydney** 74 Glendenning Road Glendenning NSW 2761 **Melbourne** 374 Hammond Road Dandenong VIC 3175 Perth 83 Bannister Road Canning Vale WA 6155 **Genie United States**

Distributed by:

18340 NE 76th Street P.O. Box 97030 Redmond, Washington 98073-9730

Effective Date: April, 2009. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries. Genie is a Registered Trademark of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Company. © 2009 Terex Corporation.