S4390/5290RT ROUGH TERRAIN SCISSORS



PRELIMINARY



- Large work area with twin
 roll-out deck extensions
- Powerful 4x4 drive
- Superb rough terrain capabilities
- Ideal for construction applications



ROUGH TERRAIN SCISSORS

DIMENSIONS	S4390RT	\$5290RT
Max. working height	15.0m	18.0m
Max. platform height (A)	13.0m	16.0m
Platform size (stowed) (B)	1.83m x 4.0m	1.83m x 4.0m
Platform size (extended) (C)	1.83m x 6.60m	1.83m x 6.60m
Deck extension (each)	1.30m	1.30m
Overall width (D)	2.27m	2.27m
Overall length (E)	4.88m	4.88m
Stowed height (F)	2.98m	3.15m
Min. height (guardrails folded)	2.25m	2.45m
Ground clearance	220mm	220mm

PERFORMANCE			
Platform capacity (SWL)	680kg	680kg	
Max. drive height	9.0m	9.0m	
Max. drive speed (stowed)	6.0km/h	6.0km/h	
Max. drive speed (elevated)	1.1km/h	1.1km/h	
Raise/lower time	94/77 sec	114/94 sec	
Gradeability	50%	40%	
Max. outrigger levelling, front to rear	7°	7°	
Max. outrigger levelling, side to side	12°	12°	
Inside turning radius	2.04m	2.04m	
Outside turning radius	5.20m	5.20m	
Tyres	33 x 12.2 high grip, solid cushion		
Controls	Proportional joystick		
Drive system	4 wheel drive		


Ρ	O١	N	EI	R	
г	U)	11	-	r.	

Power source	Perkins 404D22 diesel 38kW		
Auxiliary power unit	12V DC	12V DC	


WEIGHT

Gross weight	7,800kg	8,700kg

TURNING RADIUS



S4390/5290RT PRELIMINARY



STANDARD FEATURES

- Twin manual deck extensions
- Twin self-closing platform gates •
- 4 manually operated hydraulic outriggers •
- Oscillating axle •
- Slide-out engine tray •
- Tilt alarm and cut-out
- Horn
- Hour meter
- Power line to platform (no sockets)
- DC emergency operation •
- Integrated diagnostics
- Platform overload protection
- CE approved •

OPTIONS

- Special paint colours
- Auto-level hydraulic outriggers •
- Flashing amber beacon •
- Platform work lights •
- Hydraulic generator
- Hydraulic oil cooler
- Hydraulic welder
- Compressed air line to platform



2/26 Redfern Street, Wetherill Park. NSW 2164, Australia t: +61 1300 900 700

e: sales.au@snorkellifts.com