SPM20

SELF PROPELLED MAST LIFT



- Highly manoeuvrable selfpropelled mast lift
- Skid steer for working in tight spaces
- Easy to use and maintain
- Ideal for stockpicking and warehouse duties
- Compact and lightweight



SELF PROPELLED MAST LIFT


DIMENSIONS	SPM20
Max. working height	8.0m
Max. platform height (A)	6.0m
Platform length	0.70m
Platform width	0.78m
Stowed platform deck height (E)	0.55m
Overall width (B)	0.79m
Overall length (C)	1.36m
Stowed height (D)	1.98m
Guardrail height	1.10m
Toeboard height	0.15m
Ground clearance	50mm

PERFORMANCE	
Platform capacity (SWL)	150kg
Max. drive speed (stowed)	4.0km/h
Max. drive speed (elevated)	1.1km/h
Max. operating wind speed	Om/s
Raise/lower time	43/35 seconds
Max. operating slope	1.5°
Gradeability	25%
Inside turning radius	0m
Wheels	230mm x 80mm rear, 203mm front
Controls	Proportional single joystick
Drive system	2 x 24V 0.4kw direct drive motors


POWER	
Power source	24V DC
Battery	2 x 12V 100Ah
Charger	24V / 12A

WEIGHT	
Gross weight	1,030kg

TURNING RADIUS



SPM20



STANDARD FEATURES

- Automatic pot-hole protection
- Battery charge indicator
- Driveable at full height
- Hour meter
- Forklift pockets
- Diagnostics at platform
- Low voltage alarm
- Non-marking wheels & castors
- Proportional joystick controls
- Horn
- Tilt alarm and cut-out
- Integrated automatic battery charger 110-230V
- Sealed for life batteries
- CE approved

OPTIONS

- Special paint colours
- Flashing amber beacon
- Extending platform



2/26 Redfern Street, Wetherill Park, NSW 2164, Australia t: +61 1300 900 700

e: sales.au@snorkellifts.com